

In the Claims:

1. (original) An electromechanical sub-assembly (1) with
a control module (2) equipped with first contacts
(2.1),
a mechanical module (4) equipped with second contacts
(4.1),
a support module (3) for fixing the control module (2)
and the mechanical module (4), wherein the support module
(3) comprises
first terminals (3.1) for contacting the first
contacts (2.1),
second terminals (3.2) for contacting the second
contacts (4.1) and
at least one connection device (3.3) for contacting
the electromechanical sub-assembly (1).
2. (original) An electromechanical sub-assembly according to
claim 1, characterized in that the support module (3)
contains an electrically non-conducting material.

Claims 3 to 12 (canceled).

13. (new) An electromechanical sub-assembly according to claim
1, characterized in that the support module (3) contains
pressed screens (3.4) for electrical connection of the at

least one connection device (3.3), the first terminals (2.1) and the second terminals (4.1).

14. (new) An electromechanical sub-assembly according to claim 1, characterized in that the electromechanical sub-assembly (1) containing the control module (2), the mechanical module (4) and the support module (3) comprises an approximate cuboidal structural form equipped with corner regions.

15. (new) An electromechanical sub-assembly according to claim 14, characterized in that in the corner regions of the electromechanical sub-assembly (1) at least four recesses are placed, wherein two recesses are embodied as a screwing hole (9.1) for connecting the control module (2), the mechanical module (4) and the support module (3) and wherein at least two other recesses are embodied as a fixing hole (9.2) for fixing the electromechanical sub-assembly (1).

16. (new) An electromechanical sub-assembly according to claim 1, characterized in that the control module (2) contains a thermal conductive, metalliferous material, and that a circuit arrangement (2.2) comprising the first contacts (2.1) is mounted onto this material.

- 1 **17.** (new) An electromechanical sub-assembly according to claim
2 1, characterized in that the control module (2) comprises
3 a lid for covering the electromechanical sub-assembly.
- 1 **18.** (new) An electromechanical sub-assembly according to claim
2 1, characterized in that in the mechanical module (4) a
3 plurality of actors (6) and sensors (5) forming a closed
4 loop is provided.
- 1 **19.** (new) An electromechanical sub-assembly according to claim
2 18, characterized in that the closed loop is arranged in
3 the circuit arrangement (2.2) of the control module (2).
- 1 **20.** (new) An electromechanical sub-assembly according to claim
2 1, characterized in that the control module (2), the
3 mechanical module (4) and the support module (3) in their
4 assembled state form a housing which is waterproof towards
5 the periphery.
- 1 **21.** (new) An electromechanical sub-assembly according to claim
2 1, characterized in that at least one of the connection
3 devices (3.3) forms an external terminal (3.3) of the
4 electromechanical sub-assembly (1).
- 1 **22.** (new) An electromechanical sub-assembly according to claim
2 1, characterized in that the terminals (3.1, 3.2) and
3 contacts (2.1, 4.1) each form a terminal block (3.1, 3.2)
4 or a contact block (2.1, 4.1), respectively.